

Harlequin Flexity Plus™




Harlequin Flexity Plus is a cost-effective, self-install sprung floor panel system, designed for permanent or semi-permanent installation. Panels are laid in a brickwork fashion onto the sub-floor, so that cross joints do not coincide. The panels join together by a special tongue and groove, which are glued together for permanent installation or fixed using woodscrews at predetermined points along the tongue and groove for a semi-permanent solution.

Harlequin Flexity Plus can be installed by anyone with basic DIY skills and full instructions are provided. It's a cost-effective choice, helping to reduce the injury risks associated with dancing or performing on a hard, unsprung floor.

Harlequin Flexity Plus is finished by choosing an appropriate Harlequin vinyl performance floor or an engineered wood finish.

Specification guide

Permanent or Portable	Permanent or Semi permanent
Floor panel size	1.125m x 2.250m
Dance surface size	1.089m x 2.214m
Minimum floor thickness (before inclusion of chosen finish)	37mm
Minimum floor weight (before inclusion of chosen finish)	11.85kg/m ²
Average shock absorption	67%
Maximum point load (BS EN 1195)	1126kg



If you would like further information, advice and samples please contact us on +61 (2) 9620 7770 or auscontact@harlequinfloors.com



HARLEQUIN
www.harlequinfloors.com